

PUMPS SO WILD, THEY HOWL!

Enter the electrifying new products from Monkey Pumps: Black Howler and Red Howler. Get 'em! Love 'em! Pump 'em!



BLACK HOWLER Model E-01 12 GPD @ 250 PSI RED HOWLER Model E-02 33 GPD @ 150 PSI

www.monkeypumps.com

Features

- Manual Control by on-line adjustable stroke rate and stroke length
- Agency Approved for demanding outdoor and indoor applications
- Highly Reliable timing circuit
- Circuit Protection against voltage and current upsets
- Solenoid Protection by thermal overload with auto-reset
- Water Resistant, excellent for outdoor and indoor applications
- Internally Dampened to Reduce Noise, very acceptable for household installations
- Guided Ball Check Valve Systems, to reduce back flow and enhance outstanding priming characteristics
- Premium Standard Wetted Component Materials
- Few Moving Parts and Wall Mountable
- Safe & Easy Priming with durable leak-free bleed valve assembly


Operating Benefits

Controls

- Reliable metering performance
- Manual Stroke Rate 10:1 Ratio
- Rated "hot" for continuous duty
- Manual Stroke Length 10:1 RatioTotal Turndown Ratio 100:1 Ratio
- High viscosity capacity
- Leak-free, sealless, liquid end.

Dimensions

Model	А	В	с	D	Е	Shipping Weight
Black Howler	5.0"	9.6"	9.5"	6.5"	8.2"	10 lbs
Red Howler	5.0"	9.9"	9.5"	6.5"	8.5"	10 lbs



NOTE: inches x 2.54 = cm

Spec	Units	Black Howler	Red Howler
	GPD	12	33
Flow Rate	GPH	0.5	1.375
	LPH	1.9	5.2
Pressure Rating	PSI	250	150
	Bar	17	10
Stroke Rate	SPM	250	250
Max Viscosity	cps	1000	1000
Fluid Connection	Size	Tubing: .25" I.D.X. .38 O.D.	.25" FNPT
Fluid End Materials	Head & Valves	PVDF	316SS
	Seats & O-rings	TFE	TFE
	Check Balls	Ceramic	Ceramic





